



U.S. Department
of Transportation
**Federal Aviation
Administration**

Advisory Circular

Subject:

Date: 2/14/90
Initiated by: AIR-120

AC No: 20-134
Change:

TEST PROCEDURES FOR MAXIMUM
ALLOWABLE AIRSPEED INDICATORS

1. PURPOSE. This advisory circular provides guidance concerning test procedures which may be used in showing compliance with the standards in Technical Standard Order C46a.
2. REFERENCE. Technical Standard Order (TSO) C46a, Maximum Allowable Airspeed Indicator Systems.
3. CANCELLATION. Advisory Circular 37-2A, Test Procedures for Maximum Allowable Airspeed Indicators, dated 10/22/74, is cancelled.
4. TEST PROCEDURES.
 - a. Test procedures set forth in the Society of Automotive Engineers (SAE) Aeronautical Standard (AS) 418A dated May 15, 1961, "Maximum Allowable Airspeed Instrument, Reciprocating Engine Powered Aircraft," or SAE AS 437 dated April 15, 1963, "Maximum Allowable Airspeed Instrument, Turbine Powered Subsonic Aircraft," may be used for the purpose of showing compliance with related standards in TSO-C46a. However, environmental limits, or other limits, specified in these procedures must be adjusted if necessary to agree with those specified in TSO-C46a. Both aeronautical standards may be obtained from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, Pennsylvania 15096.
 - b. Other test procedures may also be adequate and valid for the purpose.

William J. Sullivan
Assistant Director, Aircraft
Certification Service

U.S. Department
of Transportation
**Federal Aviation
Administration**

800 Independence Ave., S.W.
Washington, D.C. 20591

**FORWARDING AND RETURN
POSTAGE GUARANTEED**

Official Business
Penalty for Private Use \$300

BULK MAIL
POSTAGE & FEES PAID
FEDERAL AVIATION
ADMINISTRATION
PERMIT NO. G-44